

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
6 March 2003 (06.03.2003)


PCT

(10) International Publication Number
WO 03/019217 A1

- (51) International Patent Classification⁷: **G01R 33/09** (71) Applicant (for DE only): **PHILIPS CORPORATE INTELLECTUAL PROPERTY GMBH [DE/DE]**; Weissshausstrasse 2, 52066 Aachen (DE).
- (21) International Application Number: **PCT/IB02/03445**
- (22) International Filing Date: **22 August 2002 (22.08.2002)** (72) Inventor; and (75) Inventor/Applicant (for US only): **BUCHHOLD, Reinhard [DE/NL]**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (25) Filing Language: **English**
- (26) Publication Language: **English** (74) Agent: **PETERS, Carl, H.**; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (30) Priority Data: **101 41 371.8** **23 August 2001 (23.08.2001)** **DE** (81) Designated States (national): **JP, US.**
- (71) Applicant (for AT, BE, BG, CH, CY, CZ, DK, EE, ES, FI, FR, GB, GR, IE, IT, JP, LU, MC, NL, PT, SE, SK, TR only): **KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]**; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (84) Designated States (regional): **European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR).**
- Published:
— with international search report

[Continued on next page]

(54) Title: **MAGNETORESISTIVE SENSOR**



(57) Abstract: To provide a magnetoresistive sensor comprising at least one sensor element for measuring a magnetic field, and a magnet assigned to the sensor element, which has a simple structure and in which subsequent trimming for compensating an offset can be dispensed with, the magnet (14) has structures (18) which lead to a perpendicular guidance of magnetic flux lines (25) from the supporting magnet (14) in the sensing direction (y direction) at least in the sensitive area (26) of the sensor (100).



WO 03/019217 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Magnetoresistive sensor

FIELD OF THE INVENTION

The invention relates to a magnetoresistive sensor comprising at least one sensor element for measuring a magnetic field, and a supporting magnet assigned to the sensor element.

5 BACKGROUND OF THE INVENTION

It is known to use magnetoresistive sensors as proximity sensors, motion sensors or position sensors. In the sensors, an external magnetic field is utilized, which produces a proportional voltage signal of the sensor element when the position of the object to be detected changes relative to the source of the external magnetic field. Such
10 magnetoresistive sensors are used, for example, for detecting reference marks in crankshaft angle measurements.

The sensor elements measuring the magnetic field do not usually operate in their saturation range and are based on the principle of the anisotropic magnetoresistive effect. It is therefore known to superimpose on these sensor elements a magnetic field
15 stabilizing the transfer characteristic, which magnetic field is usually produced by a supporting magnet assigned to the sensor element. In the case of passive, ferromagnetic objects to be detected, the magnet is further used for the purpose of providing an operating field whose change is detected under the influence of the object. The magnet and the sensor element are then in a defined fixed position relative to each other. It is known that already
20 slight positioning tolerances between the sensor element and the magnet in the sensitive direction lead to an offset of the characteristic curve of the sensor element. This characteristic curve offset must be compensated by subsequent trimming of the magnetoresistive sensor.

OBJECT AND SUMMARY OF THE INVENTION

25 It is therefore an object of the invention to provide a magnetoresistive sensor which has a simple structure and does not require subsequent trimming for offset compensation.

According to the invention, this object is solved by a magnetoresistive sensor as defined in claim 1. Since the magnet has structures, preferably on its surface assigned to

the at least one sensor element, which structures lead to a perpendicular guidance of magnetic flux lines in the sensitive range, it is advantageously achieved that only minimal magnetic fields, which might lead to an offset of the characteristic curve of the sensor element, occur in the positioning plane between the sensor element and the magnet in the sensitive direction.

5 When the supporting magnet according to the invention is used, subsequent trimming of the magnetoresistive sensor is thus not necessary.

In a preferred embodiment of the invention, the structures are formed in such a way that a perpendicular guidance of the magnetic flux lines of the magnet with respect to the positioning plane is maintained in the sensor area. As a result, minimal magnetic fields in the
10 sensitive direction of the positioning plane can be achieved in an optimal manner.

In a preferred embodiment of the invention, the surface structures are constituted by trough-shaped indentations of the magnet, in which the at least one sensor element is arranged. In accordance with preferred embodiments, the trough-shaped indentations are constituted by plane surfaces or concave surfaces with respect to the
15 positioning plane. It is achieved in a simple manner by such an embodiment that magnetic fields in the positioning plane can be optimally minimized in the positioning area of the sensor elements.

In addition to the fact that magnetic trimming of the magnetoresistive sensor can be dispensed with, anisotropic magnetic materials may be used for the magnets in the
20 embodiments according to the invention. These materials are distinguished by their high magnetic long-time stability. Finally, the measuring accuracy of the magnetoresistive sensor is enhanced because of the absence of trimming and thereby a possible trimming error.

BRIEF DESCRIPTION OF THE DRAWINGS

25 These and other aspects of the invention are apparent from and will be elucidated with reference to the embodiments described hereinafter.

In the drawings:

30 Figs. 1 and 2 show a magnetoresistive sensor in a diagrammatic plan view and side elevation;

Figs. 3 to 6 are different diagrammatic perspective views of sensors according to the invention, and

Fig. 7 shows a magnetic field distribution of the supporting magnet according to the invention, shown in Fig. 3.

DESCRIPTION OF EMBODIMENTS

5 Figs. 1 and 2 show a magnetoresistive sensor 100. The sensor 100 comprises at least a sensor element 12 which is assigned to a magnet 14. Sensor element 12 and magnet 14 are flexibly connected together in an appropriate manner, for example, glued to each other. A sensor element 12 is herein understood to mean a sensor chip which may comprise a plurality of magnetoresistive ranges (resistances) in a bridge circuit configuration.

10 Furthermore, the sensor chip may comprise integrated electronic components for evaluating the sensor signals.

 For the purpose of clarity, a system of co-ordinates is incorporated in the Figures. It can be seen from Figs. 1 and 2 that an x/y plane extends parallel to a surface 16 of the magnet 14. The surface 16 simultaneously constitutes the positioning plane for the sensor

15 element 12 on the supporting magnet 14. An x/z plane subtends perpendicularly to the surface 16, in which the magnetization vector of the magnet is situated. An y/z plane also subtends perpendicularly to the surface 16, but is 90° rotated with respect to the x/z plane.

 The sensitive direction of the sensor 100 is the y direction. This means that, in the case of an approach to an external magnetic field, for example, by a reference magnet

20 during measurement of a crankshaft angle, this magnet is moved in the y direction past the sensor 100. The approach and the instantaneous position of the reference magnet and thus, for example, the position of the crankshaft can thereby be detected.

 Figs. 3 to 6 show four different variants of the magnet 14. As is shown in these Figures, the surface 16 has structures 18 which are essentially constituted by trough-shaped

25 indentations 20. In accordance with the embodiment shown in Fig. 3, the trough-shaped indentation 20 has a plane bottom surface 22 on which the sensor element 12 is arranged. In accordance with the embodiment shown in Fig. 4, the surface 22 is provided with a pedestal-like elevation 24 on which the sensor element 12 is arranged.

 Fig. 5 shows a variant in which the magnet 14 has a convex symmetrical shape

30 with respect to the sensor element 12, while the surface 22 is convex in the y direction. In the area of the sensor chip 12, the surface 22 is, however, plane. An analog variant is shown in Fig. 6 in which the surface 22 is convex in the x direction. Furthermore, the supporting magnet 14 is wedge-shaped in the x direction.

Embodiments other than the ones shown in the Figures are possible within the scope of the invention. Differently chosen structures of the magnets 14 are of course also feasible when it is thereby achieved that the magnetic flux lines 25 of the magnet 14 perpendicularly to the surface 16, i.e. perpendicularly to the x/y plane, emerge from the magnet 14 in the area of the sensor element 12.

This is shown by way of example in Fig. 7 with reference to the magnet 14 shown in Fig. 3. The Figure is a sectional view of the magnet 14 with the indentation 20 constituting the structure 18. In this representation, the plane of the drawing coincides with the y/z plane. It is clear from the Figure that the indentation 20 deflects the magnetic flux lines 25 outside the magnet 14 in such a way that the magnetic flux lines 25 emerge essentially perpendicularly to the surface 16 without any deflection in the y direction in the sensitive area 26, i.e. in the area in which the sensor element 12 is arranged. This leads to only a minimal magnetic field H_y in the sensitive area 26. This quasi-unavailable magnetic field H_y can therefore not lead to an offset of the sensor element 12 in its sensing direction, i.e. in the y direction.

CLAIMS

1. A magnetoresistive sensor comprising at least one sensor element for measuring a magnetic field, and a magnet assigned to the sensor element, characterized in that the magnet (14) has structures (18) which lead to a perpendicular guidance of magnetic flux lines (25) from the magnet (14) in the sensing direction (y direction) at least in the sensitive area (26) of the sensor (100).
5
2. A magnetoresistive sensor as claimed in claim 1, characterized in that the structures (18) are formed in a surface (16) facing the at least one sensor element (12).
- 10 3. A magnetoresistive sensor as claimed in any one of the preceding claims, characterized in that the magnetic flux lines (25) are guided perpendicularly with respect to the surface (positioning plane) (16) in the sensitive area (26).
4. A magnetoresistive sensor as claimed in any one of the preceding claims,
15 characterized in that the surface (16) comprises a trough-shaped indentation (20) in which the sensor element (12) is arranged.
5. A magnetoresistive sensor as claimed in any one of the preceding claims,
20 characterized in that the indentation (20) has a plane bottom surface (22).
6. A magnetoresistive sensor as claimed in any one of the preceding claims, characterized in that the bottom surface (22) constitutes a pedestal-like elevation (24) for accommodating the sensor element (12).
- 25 7. A magnetoresistive sensor as claimed in any one of the preceding claims, characterized in that the indentation (20) has a concave shape.

8. A magnetoresistive sensor as claimed in claim 7, characterized in that the concave shape extends in the y direction.

5 9. A magnetoresistive sensor as claimed in claim 7, characterized in that the concave shape extends in the x direction.

10. A magnetoresistive sensor as claimed in any one of the preceding claims, characterized in that the overall magnet (14) is concave-shaped with respect to the surface (16).
10

11. A magnetoresistive sensor as claimed in any one of the preceding claims, characterized in that the supporting magnet (14) is wedge-shaped.

1/3

100




FIG.1

100




FIG.2




FIG.3




FIG.4

2/3




FIG. 5




FIG. 6

3/3




FIG. 7

INTERNATIONAL SEARCH REPORT

 International Application No
 PCT/IB 02/03445

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 G01R33/09		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 G01R G01D		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the International search (name of data base and, where practical, search terms used) EPO-Internal		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 107 793 A (YOKOTANI MASAHIRO ET AL) 22 August 2000 (2000-08-22) column 6, line 11 - line 23; figure 2	1-3,7-10
Y	-----	4-6
Y	US 6 043 646 A (JANSSEUNE LUC) 28 March 2000 (2000-03-28) column 1, line 66 - column 2, line 15	4,5
Y	DE 199 41 860 A (SIEMENS AG) 29 March 2001 (2001-03-29) figure 1B	6
X	US 5 637 995 A (IZAWA ICHIRO ET AL) 10 June 1997 (1997-06-10) column 9, line 38 - line 63; figure 29	1-4
	----- -/--	
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the International filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the International filing date but later than the priority date claimed "T" later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family		
Date of the actual completion of the International search		Date of mailing of the International search report
19 November 2002		26/11/2002
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer Swartjes, H

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IB 02/03445

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 712 064 A (ECKARDT DIETER ET AL) 8 December 1987 (1987-12-08) column 2, line 67 -column 3, line 22 -----	1-4
X	US 5 585 719 A (ENDO MICHIKO ET AL) 17 December 1996 (1996-12-17) column 13, line 24 - line 55 -----	1-3

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 02/03445

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6107793	A	22-08-2000	JP 10221114 A DE 19729808 A1	21-08-1998 13-08-1998
US 6043646	A	28-03-2000	DE 9414104 U1 WO 9607112 A1 DE 59504833 D1 EP 0778954 A1 ES 2128756 T3 JP 2921603 B2 JP 9511357 T	03-11-1994 07-03-1996 25-02-1999 18-06-1997 16-05-1999 19-07-1999 11-11-1997
DE 19941860	A	29-03-2001	DE 19941860 A1 DE 29923913 U1	29-03-2001 28-06-2001
US 5637995	A	10-06-1997	JP 6174490 A JP 3170916 B2 JP 6186240 A JP 7260813 A JP 8005647 A DE 4341890 A1 JP 7027571 A	24-06-1994 28-05-2001 08-07-1994 13-10-1995 12-01-1996 16-06-1994 27-01-1995
US 4712064	A	08-12-1987	DE 3426784 A1 DE 3574282 D1 WO 8600877 A1 EP 0226574 A1 JP 61502783 T	30-01-1986 21-12-1989 13-02-1986 01-07-1987 27-11-1986
US 5585719	A	17-12-1996	JP 3186403 B2 JP 7004988 A DE 4407565 A1	11-07-2001 10-01-1995 15-09-1994